

-----PRE CLONE-----

1. login as applmgr and set the ERP environment using the env file, usually the format <sid\_hostname>.xml
2. check the perl version perl -v - should be > 5.005
3. check the perl location using command - which perl, it should be pointing to iAS home perl executable
4. cd to \$COMMON\_TOP/admin/scripts

**perl adpreclone.pl appsTier**

5. supply the apps password.

SURENDER  
SARA

**PRECLONE STEPS - DB TIER**

1. login as oracle and set the 9i/10g environment using the env file, usually the format <sid\_hostname>.xml
2. check the perl version perl -v - should be > 5.005
3. check the perl location using command - which perl, it should be pointing to 9i/10g home perl executable
4. cd to \$ORACLE\_HOME/appsutil/bin

**perl adpreclone.pl dbTier**

5. supply the apps password.

```
Source applmgr >
  APPL_TOP, COMMON_TOP, IAS, 806 TO Target applmgr
Source oracle >
  9i/10g home TO Target oracle
--- login as applmgr
cd $APPL_TOP
scp -R <APPL_TOP> applmgr@<Target_Machine>:/u01/applmgr ( location
of APPL_TOP)
```

-----POST CLONE-----

POST CLONE... MAKE SURE THERE IS clone directory created in the TARGET system.  
Use the post clone scripts from that dir.

Post clone has to be done on DB tier first as for appsTier you will need the database to be up.

**POSTCLONE STEPS - DB TIER**

1. login as oracle and set the 9i/10g environment using the env file, usually the format <sid\_hostname>.xml
2. check the perl version perl -v - should be > 5.005
3. check the perl location using command - which perl, it should be pointing to 9i/10g home perl executable

**NEXT STEP CRITICAL**

4. Make sure that the contrl files listed in the paramter CONTROL\_FILES located inside init<sid>.ora file, are removed.
5. MAKE SURE DB is DOWN all the way.
6. cd to \$ORACLE\_HOME/appsutil/clone/bin

**perl adcfgclone.pl dbTier**

5. supply the apps password.

**POSTCLONE STEPS - APPSTIER**

1. login as applmgr and set the ERP environment using the env file, usually the format <sid\_hostname>.xml
2. check the perl version perl -v - should be > 5.005
3. check the perl location using command - which perl, it should be pointing to iAS home perl executable
4. cd to \$COMMON\_TOP/clone/scripts

**perl adcfgclone.pl appsTier**

5. supply the apps password.

Enter all the questions about your placement of iAS, 806, APPL\_TOP, COMMON\_TOP directory locations...